



GAIN AND OFFSET ADJUSTMENTS SEALED (CODE 'Y')




IP67 SHORT CABLE GLAND (CODE 'Mxx')



NOTE: SENSORS ARE MADE IN FOUR STANDARD LENGTHS.

TRAVEL: (mm)	BODY LENGTH: (mm)
CALIBRATED MECHANICAL 'X'	STANDARD 'Y' FLANGE
0-51 TO 0-70	70 125.0 141.3
0-71 TO 0-100	100 155.0 171.3



ELECTRICAL OPTIONS/ SPECIFICATIONS

OUTPUT OPTION	A	B	C	D	E	F	G	H	SUPPLY
	0.5 TO 4.5V RATIO METRIC	±5V	0.5 TO 9.5V	±10V	0.5 TO 4.5V	4 TO 20mA 2-WIRE	4 TO 20mA 3-WIRE SINK	4 TO 20mA 3-WIRE SOURCE	5V
		±15V				24V	24V	24V	24V
						24V	24V	24V	24V
						24V	24V	24V	24V
						24V	24V	24V	24V

SINK VERSION OUTPUT COMPLIANCE 5-28V
SOURCE VERSION DRIVE 300Ω MAX TO 0V

CABLE: 0.2mm², O/A SCREEN, PUR JACKET - SUPPLIED WITH 50cm OR REQUIRED LENGTH IN cm. e.g. 'L50'

3-CORE: JACKET Ø4mm
4-CORE: JACKET Ø4.6mm

CABLE/CONNECTOR* CONNECTIONS:
3 CORE 4 CORE CONNECTOR

RED	RED	:1	+Ve
BLACK	GREEN	:3	0V
	YELLOW	:4	-Ve - OPTIONS: B OR D
WHITE	BLUE	:2	OUTPUT
SCREEN	SCREEN	:4	BODY - OPTIONS: A, C, E-H

*CONNECTORS; MAXIMUM CONDUCTOR CROSS SECTION 0.75mm²
RANGE OF DISPLACEMENT FROM 0-51mm TO 0-100mm e.g.76, IN INCREMENTS OF 1mm.


BODY MATERIAL: STAINLESS STEEL.
FLANGE MATERIAL: ALUMINIUM (CODE 'N')

FURTHER OPTIONS:

SINGLE PAIR OF BODY CLAMPS (CODE 'P')
SPRUNG PLUNGER, TO EXTENDED POSITION (CODE 'R')
DOME END (CODE 'T') IN CONJUNCTION WITH SPRUNG PLUNGER (CODE 'R')**

PLUNGER FREE (CODE 'V')

N.b. NOT AVAILABLE WITH SPRUNG OPTIONS.



A	FIRST ISSUE - RAN1063	PDM
B	RANGE NOTE AMENDED ~ RAN1200	PDM



THE PLUNGER RETRACTS 5mm FROM START OF CALIBRATED TRAVEL (2mm FOR SPRUNG VERSIONS) AND EXTENDS 9.5mm* BEYOND END OF MECHANICAL TRAVEL. *DOES NOT INCLUDE DIFFERENCE BETWEEN CALIBRATED AND MECHANICAL TRAVEL, DIMENSIONS ARE NOMINAL. 'V' CODED PLUNGER WILL DEPART SENSOR BODY.

DRAWINGS NOT TO BE CHANGED WITHOUT REFERENCE TO THE CHANGE PROCEDURE.
CHANGES TO PARTS USED IN INTRINSICALLY SAFE PRODUCT MUST BE APPROVED BY THE AUTHORISED PERSON
THIS IS AN UNCONTROLLED PRINT AND WILL NOT BE UPDATED.

Herbertek www.herbertek.se
info@herbertek.se
+46-18 590510

POSITEK
P
LIMITED

A	10/11/15	CHECKED BY	X	±0.4
B	29/08/17	RDS	X.X	±0.2
			X.XX	±0.1
				DIMS mm
DESCRIPTION				
P133 LIPS MID STROKE LINEAR POSITION SENSOR				
SCALE				
10mm				
DRAWING NUMBER P133-11 REV B				
SHEET 1 OF 1				